

## STUD WELDING PRODUCTS, INC

## CAPACITOR DISCHARGE (CD) 5/16" WELDERS

will shoot studs up to 5/16" in diameter







FEATURES	StudPro 3125Xi	CDi 2302	Lynx 4 Modular
DESCRIPTION	Easy to use and only weights 20 lbs. Intui- tive Touchscreen Interface with Preset val- ues for fast, accurate, and repeatable weld settings. Our most popular brand.	German made with self forming capacitors to provide alonger life perido and higher reliability. Easy to use and compact design.	The modular is microprocessor controller with an improved charging circuit and height output transformer which maximizes its duty cycle.
WELD RANGE	14ga - 5/16"	14ga - 5/16"	#4 - 5/16"
DUTY CYCLE	5/16" = 14 Studs/min	5/16"-12 Studs/min	5/16"=6 Studs/min
CAPACITANCE	114,000 μF	99,000 μF	81,000 μF
PRIMARY POWER	110 VAC @ 50/60 HZ 15 AMP 220 VAC @50/60 HZ 7.5 AMP	230 V/115 V*, 50/60 Hz, 10 AT	115/230 50/60Hz
CHARGE VOLTAGE	35-200 VDC	50 to 220 V stepless voltage regulation	50-195 stepless Voltage Regulation
SIZE	14" L X 111" W X 12" H	19" L x 8" W x 10" H	12" L x 12" W x 5" H
POWER UNIT WEIGHT	21 lbs	37 lbs	26 lbs
GUN CABLE LENGTH	#4 x 25'	#2 x 21'	#2 x 10'
GROUND CABLE LENGTH	#4 x 15' double	#2 x 8' double	#2 x 10' double