

STUD WELDING PRODUCTS, INC

CAPACITOR DISCHARGE (CD) 1/4" WELDERS

will shoot studs up to 1/4" in diameter









FEATURES	StudPro 2500Xi	CDi 1502	Pegasar 500	Lynx4 Quickshot
DESCRIPTION	Intuitive touchscreen with preset values. Adjustable settings perfect for your needs. Our most popular CD welder.	German made with efficient inverter capacitor charging technology	Battery powered, light weight and easy to use. Inverter technology for quick recharg- ing times	Comes with a portable carring case, New and improved charging technology.
WELD RANGE	#4 to 1/4"	#4 to 1/4"	#4 to 1/4"	#4 to 1/4"
DUTY CYCLE	1/4"= 18 Studs/Min	1/4"= 14 Studs/Min	1/4"= 20 Studs/Min	1/4"= 8 Sstuds/Min
CAPACITANCE	76,000 μF	66,000 μF	100,000 μF	54,000 μF
PRIMARY POWER	110 VAC @ 50/60 HZ 15 AMP 220 VAC @50/60 HZ 7.5 AMP	115V 50/60Hz 10AT	100V TO 240V, 50/60 Hz In Battery operation: 25.55V	50-195 Stepless Voltage Regulation- 115/230 50/60Hz
CHARGE VOLTAGE	35-200 V	220 V min	50 to 100 V stepless voltage regulation	50-195 V stepless voltage regulation
SIZE	14" L X 10.5"W X 11.5"H	15.75"L x 8.07"W x 9.84"H	18"L x 11"W x 14"H	12"L x 12"W x 5"h
POWER UNIT WEIGHT	18 lbs	30.8 lbs	26 lbs with Battery 24 lbs without Battery	24 lbs
GUN CABLE LENGTH	#4 x 25'	#2 x 21'	#2 x 10'	#2 x 10'
GROUND CABLE LENGTH	#4 X 15' double	#2 x 8' double	#2 x 8' single	#2 x 10' double