## STUD WELDING PRODUCTS, INC

your number one stud









## DESCRIPTION

The TW5500 is a fully integrated stud welding system for ferrule-shielded and gas-shielded drawn arc stud welding. The TW5500 contains digital controls for weld time, weld current, and gas purge time. The system was designed to be a perfect fit for welding up through 5/8" diameter studs. This is all contained in a compact, portable package. **New** Pro-Tech'd technology protects the gun circuitry. **New** improved user interface for more intuitive setup. **New** factory presets and user customizable presets. **New** improved weld control.

*Includes:* TW5500 power supply, TWE18500 Med Duty stud gun, 35 feet starter combo cable, and 25 feet ground cable assembly

FEATURES	TW5500
WELD RANGE	1/4" - 5/8" diameter studs
DUTY CYCLE (studs per minute)	5. V 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.
INPUT VOLTAGE	230v/120a or 460v/60a or 575v/50a VAC 3-Phase 60Hz
DIMENSIONS	30" x 25" x 22"
WEIGHT	Machine Only 445 lbs / Complete Ready to Ship 650 lbs
STANDARD GUN MODEL	TWE18500 Med Duty Gund
COMBO CABLE SIZE	35' Starter Combo Cable
GROUND CABLE SIZE	25' Ground Cable Assembly
TOTAL OUTPUT (AMPS)	1400